

Easton Round

Round Front, Vitreous China Two-Piece Toilet



FEATURES

- Contemporary design
- 1.6 Gpf / 6.0 Lpf
- TotalFlush™ flushing technology for a reliable flush first time — every time.
- 2" glazed trapway
- Available in White and Bone
- Upgrade with a color-match SmartClose™ or Primo™ toilet seat
- Outstanding protection — The Mansfield® limited lifetime warranty

Model No.	Description	Approx. Wt.
	Round front, (1.6 Gpf/6.0 Lpf) two-piece toilet. 12" rough-in. Includes tank trim and front-mount, color-match plastic trip lever. Less toilet seat and supply. Specify color.	65 lbs. (29 kg)
820-10	Round front toilet bowl only. 12" rough-in. Less toilet seat. Specify color.	30 lbs. (14 kg)
820-26	Tank and cover only, with front-mount, color-match plastic trip lever. Less supply. Specify color.	30 lbs. (14 kg)
SB1100	Round, SmartClose™ toilet seat. Specify color.	5.5 lbs. (2 kg)
SB1150	Round, Primo™ toilet seat. Specify color.	5.5 lbs. (2 kg)

Shown with SB1150
Primo™ toilet seat



TotalFlush®

Easton Round

Round Front, Vitreous China Two-Piece Toilet

FEATURES & UPGRADES

TotalFlush™ Flushing Technology

This gravity fed toilet features a 1.6 gpf / 6.0 lpf anti-siphon ballcock, durable flush valve and glazed trapway. TotalFlush™ offers a complete flush the first time — every time. Ideal for residential applications or light commercial use.



89-1012 Anti-Siphon Ballcock

The 89 anti-siphon ballcock affords efficient tank toilet operation at high or low water pressures. Adjustment screws allows water level adjustment without bending the float rod. Completely non-electrolytic and non-corrosive.



202-1012 Flush Valve

The 202 flapper style flush valve provide 1.6 gpf / 6.0 lpf water conservation efficiency. Plastic construction provided non-corrosive, long-life dependability. Won't rust or corrode.



Add a Toilet Seat

With a simple touch, Mansfield's newest SmartClose™ toilet seat closes gently and quietly. Or upgrade your toilet with a popular Primo™ toilet seat. Made of durable, high impact, heavy-duty plastic. For all applications - Get More, Get Mansfield®.




TECHNICAL INFORMATION

Material	Vitreous China
Water Pressure Range	20 to 80 P.S.I
Flush System	TotalFlush™ Flushing Technology
Water Usage	1.6 Gpf / 6.0 Lpf
Water Surface Area	8-1/2" x 6-1/2"
Trap Diameter	2-1/8"
Trap Seal	2"
Rough-in	12"
Shipping Dimensions	Model 820-10 25-1/4" x 16" x 15-1/2" (645 mm x 406 mm x 394 mm) Model 820-26 18-3/4" x 8-1/8" x 14" (478 mm x 206 mm x 356 mm)
Shipping Weight	Model 820-10 - 30 lbs (14 kg) Model 820-26 - 30 lbs (14 kg)
Warranty	Vitreous China - Limited Lifetime; Tank Trim - Limited One Year

These dimensions are nominal and are subject to change without prior notice.

Fixture performance and specifications meet or exceed, ANSI/ASME A112.19.2 standards and CAN/CSA B45.0 standards, and other state and local codes.

See our complete line of acrylic and vitreous china bathroom fixtures, plastic tank trim and plumbing products.



NOTE: Install this product according to the installation guide. Fixture dimensions are nominal and conform to tolerances in ASME Standard A112.19.2